



# MATERIAL SAFETY DATA SHEET

## CHAMP X IT OUT VANDAL MARK REMOVER

1. Product And Company Identification			
<b>Supplier</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  <b>Company Contact:</b> Aludia B. Hernandez <b>Telephone Number:</b> 708-865-1000 <b>FAX Number:</b> 708-865-0923 <b>E-Mail:</b> sales@chaseproducts.com <b>Web Site:</b> www.chaseproducts.com		<b>Manufacturer</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  <b>Company Contact:</b> Aludia B. Hernandez <b>Telephone Number:</b> 708-865-1000 <b>FAX Number:</b> 708-865-0923 <b>E-Mail:</b> sales@chaseproducts.com <b>Web Site:</b> www.chaseproducts.com	
<b>Supplier Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924		<b>Manufacturer Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924	
<b>Issue Date:</b> 02/05/2007  <b>Product Name:</b> CHAMP X IT OUT VANDAL MARK REMOVER <b>Chemical Name:</b> 7-7786-1 <b>CAS Number:</b> Not Established <b>MSDS Number:</b> 3981 <b>Product Code:</b> 438-5149-8 <b>Product/Material Uses</b> - Vandal Mark Remover			
2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
ACETONE	67-64-1		
ALKANOLAMIDE	68603-42-9		
CARBON DIOXIDE	124-38-9		
D-LIMONENE	5989-27-5		
DIETHYLENE GLYCOL MONOETHYL ETHER	111-90-0		10 - 15
DIMETHYL ADIPATE	627-93-0		
DIMETHYL GLUTARATE	1119-40-0		
ETHOXYLATED ALCOHOL	68002-97-1		
HEAVY AROMATIC NAPHTHA	64742-94-5		
METHANOL	67-56-1	<	3
NAPHTHALENE	91-20-3	<	2
PINE OIL	8002-09-3		
TOLUENE	108-88-3		10 - 15
Hazardous components, according to OSHA, are listed when present at 1.0% or greater. Carcinogens are listed when present at 0.1% or greater.			
3. Hazards Identification			
<b>Primary Routes(s) Of Entry</b> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. <b>Eye Hazards</b> - Causes eye irritation. <b>Skin Hazards</b> - Causes skin irritation.			



# MATERIAL SAFETY DATA SHEET

## CHAMP X IT OUT VANDAL MARK REMOVER

### 3. Hazards Identification - Continued

**Ingestion Hazards** - Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately. This is an aerosol product, ingestion is unlikely to occur. Contains methanol, may cause blindness if swallowed.

**Inhalation Hazards** - Deliberate inhalation of concentrate vapor or mist may cause headaches, dizziness and nausea.

**Chronic/Carcinogenicity Effects** - Toluene has been associated with kidney and liver disorders. California's Proposition 65: "Warning: This product contains naphthalene, a chemical known to the State of California to cause cancer".

**Teratogenicity (Birth Defects)** - This product contains 2-ethoxyethanol (from ethoxy diglycol) and toluene. California Proposition 65: "WARNING: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm".

**Reproductive Effects** - Suspect reproductive hazard. Contains material which may cause birth defects, based on animal data. This product contains toluene and 2-ethoxyethanol.

**Neurotoxicity** - Not known


**Mutagenicity (Genetic Effect)** - Not known

**Signs And Symptoms** - Acute: Deliberate inhalation of concentrate vapor or mist may cause headaches, dizziness and nausea. Contact with skin causes irritation. Irritant to the eyes.

**Conditions Aggravated By Exposure** - May aggravate pre-existing skin, kidney, liver and respiratory disorders.

**Conditions Aggravated By Overexposure** - May aggravate pre-existing skin, kidney, liver and respiratory disorders.

### First Aid (Pictograms)



### 4. First Aid Measures

**Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**Skin** - Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

**Ingestion** - Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

**Inhalation** - If overcome by vapor move victim to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

### 5. Fire Fighting Measures

**Flash Point:** Not available °F Not available °C

**Flash Point Method:** Not available

**Lower Explosive Limit:** Not available

**Upper Explosive Limit:** Not available

**Fire And Explosion Hazards** - This product is an aerosol product for which **Flame Projection is over 18 in. with 5 in. flashback.** Temperatures above 120 F may cause cans to burst.

**Extinguishing Media** - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

**Fire Fighting Instructions** - Water spray may be used to cool cans in the vicinity of fire or excessive heat.



# MATERIAL SAFETY DATA SHEET

## CHAMP X IT OUT VANDAL MARK REMOVER

### 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

### Handling & Storage (Pictograms)



### 7. Handling And Storage

**Handling And Storage Precautions** - Store in a cool, dry place away from heat and open flame.

**Handling Precautions** - Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.

**Storage Precautions** - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B)**

**Work/Hygienic Practices** - Wash hands thoroughly after using this product.

### Protective Clothing (Pictograms)



### 8. Exposure Controls/Personal Protection

**Engineering Controls** - Use with adequate general and local exhaust ventilation.

**Eye/Face Protection** - Conventional eyeglasses to guard against splashing.

**Skin Protection** - Rubber gloves required.

**Respiratory Protection** - Use in well-ventilated area ONLY. NIOSH-approved respirator recommended. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

#### **Ingredient(s) - Exposure Limits**

ACETONE

ACGIH TLV-STEL 750 ppm ; ACGIH TLV-TWA 500 ppm ; OSHA PEL-TWA 1,000 ppm

CARBON DIOXIDE

ACGIH TLV-STEL 30,000 ppm ; ACGIH TLV-TWA 5,000 ppm ; OSHA PEL-TWA 5,000 ppm

DIMETHYL ADIPATE

PEL (OSHA) - none established ; TLV (ACGIH) - none established

DIMETHYL GLUTARATE

PEL (OSHA) - none established ; TLV (ACGIH) - none established

HEAVY AROMATIC NAPHTHA

100 ppm Recommended by the manufacturer.

METHANOL

ACGIH TLV-STEL 250 ppm (Skin) ; ACGIH TLV-TWA 200 ppm (Skin) ; OSHA PEL-TWA 200 ppm

NAPHTHALENE

ACGIH TLV-STEL 15 ppm ; ACGIH TLV-TWA 10 ppm ; OSHA PEL-TWA 10 ppm



# MATERIAL SAFETY DATA SHEET

## CHAMP X IT OUT VANDAL MARK REMOVER

### 8. Exposure Controls/Personal Protection - Continued

#### Ingredient(s) - Exposure Limits - Continued

TOLUENE

ACGIH TLV-TWA 50 ppm (Skin) ; OSHA PEL-CEILING 300 ppm ; OSHA PEL-PEAK 500 ppm

OSHA PEL-TWA 200 ppm

### 9. Physical And Chemical Properties

**Appearance** - Yellowish liquid.

**Odor** - Citrus odor.

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** Not applicable °F Not applicable °C

**Boiling Point:** Heavy Aromatic Solvent Naphtha 363-401 °F 183-205 °C

**Specific Gravity:** 0.917 to 0.927 concentrate

**Percent VOCs:** 48

**pH Factor:** NA

**Solubility:** Insoluble

**Evaporation Rate:** Faster than butyl acetate

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

**Conditions To Avoid (Stability)** - Temperatures above 120 F

**Incompatible Materials** - Avoid heat, open flame and contact with strong oxidizers.

**Hazardous Decomposition Products** - Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

**Conditions To Avoid (Polymerization)** - Temperatures above 120 F

### 11. Toxicological Information

No Data Available...

### 12. Ecological Information

**Ecotoxicological Information** - No specific ecological data is available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

### 13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** Place in trash or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

### 14. Transport Information

**Proper Shipping Name** - ORM-D Consumer Commodity

**Hazard Class**

2.1

**DOT Identification Number**

UN1950



# MATERIAL SAFETY DATA SHEET

## CHAMP X IT OUT VANDAL MARK REMOVER

### 14. Transport Information - Continued

#### DOT Shipping Label

Aerosol Consumer Commodity

### 15. Regulatory Information

**U.S. Regulatory Information** - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### **SARA Hazard Classes**

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

**SARA Section 313 Notification** - This product contains the following toxic chemicals (above the *de minimis* level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material: Diethylene Glycol Monoethyl Ether, Methanol, Naphthalene and Toluene. See section 2 for % amounts in the product.

#### **Ingredient(s) - U.S. Regulatory Information**

DIETHYLENE GLYCOL MONOETHYL ETHER

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard

METHANOL

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

NAPHTHALENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

TOLUENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

#### **Ingredient(s) - State Regulations**

ACETONE

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

CARBON DIOXIDE

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

DIETHYLENE GLYCOL MONOETHYL ETHER

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New York City - Hazardous Substance

METHANOL

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

NAPHTHALENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; Pennsylvania - Workplace Hazard; Pennsylvania



# MATERIAL SAFETY DATA SHEET

## CHAMP X IT OUT VANDAL MARK REMOVER

### 15. Regulatory Information - Continued

#### Ingredient(s) - State Regulations - Continued

- Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance


PINE OIL

New Jersey - Workplace Hazard; New York City - Hazardous Substance

TOLUENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; California - Proposition 65; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### NFPA



#### HMIS

HEALTH	*2
FLAMMABILITY	4
REACTIVITY	1
PERSONAL PROTECTION	B

### 16. Other Information

#### Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supercedes A Previous MSDS Dated: 01/08/2004

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Chase Products Co.

Printed Using MSDS Generator™ 2000