# FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

# **Material Safety Data Sheet (MSDS)**

MSDS #: 455.00

**Revision Date:** November 25, 2002

## Section 1 — Chemical Product and Company Identification

# Lithium Hydroxide

Flinn Scientific, Inc. P.O. Box 219 Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

## Section 2 — Composition, Information on Ingredients

Lithium Hydroxide

CAS#: 1310-66-3

### Section 3 — Hazards Identification

Colorless, odorless crystals.

Corrosive to eyes, skin and respiratory tract. Avoid body tissue contact.

FLINN AT-A-GLANCE

Health-1 Flammability-0 Reactivity-0 Exposure-2 Storage-1

0 is low hazard, 3 is high hazard

#### Section 4 — First Aid Measures

Call a physician, seek medical attention for further treatment, observation and support after first aid. Inhalation: Remove to fresh air at once. If breathing has stopped give artificial respiration immediately.

Eye: Immediately flush with fresh water for 15 minutes.

External: Wash continuously with fresh water for 15 minutes.

Internal: Give large quantities of water. Call a physician or poison control at once.

### Section 5 — Fire Fighting Measures

Non flammable solid.

**NFPA CODE** 

None Established

### Section 6 — Accidental Release Measures

Restrict unprotected personnel from area. Sweep up, place in sealed bag or container and dispose. Ventilate area and wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

## Section 7 — Handling and Storage

Flinn Suggested Chemical Storage Pattern: Inorganic #4. Store with hydroxides, oxides, silicates and carbonates. Store in a cool dry place. Deliquescent, store in Flinn Chem-Saf Bag. Use and dispense in a hood.

### <u>Section 8 — Exposure Controls , Personal Protection</u>

Avoid contact with eyes, skin and clothing. Wear chemical splash goggles, chemical-resistant gloves and chemical-resistant apron. Use exhaust ventilation to keep airborne concentrations low.

# FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

# **Material Safety Data Sheet (MSDS)**

Lithium Hydroxide

**MSDS #:** 455.00

**Revision Date:** November 25, 2002

## Section 9 — Physical and Chemical Properties

Colorless, odorless crystals.

Solubility: Soluble in water. Slightly soluble in alcohol.

Formula: LiOH H2O Formula Weight: 41.96 Specific Gravity: 2.54 Melting Point: 470 C

#### Section 10 — Stability and Reactivity

Avoid contact with strong oxidizers, strong acids.

Shelf life: Poor; substance hygroscopic.

### Section 11 — Toxicological Information

Acute effects: Corrosive ORL-RAT LD50: N.A. Chronic effects: N.A. IHL-RAT LC50: N.A. Target organs: N.A. SKN-RBT LD50: N.A.

N.A. = Not available, not all health aspects of this substance have been fully investigated.

#### Section 12 — Ecological Information

Data not yet available.

### Section 13 — Disposal Considerations

Please consult with state and local regulations. Flinn Suggested Disposal Method #10 is one option.

### Section 14 — Transport Information

Shipping Name: Lithium Hydroxide, solid

Hazard Class: 8, Corrosive UN Number: UN2680 N/A = Not applicable

### Section 15 — Regulatory Information

TSCA-listed, EINECS-listed (215-183-4), RCRA code D002.

#### Section 16 — Other Information

Consult your copy of the Flinn Scientific Catalog/Reference Manual for additional information about laboratory chemicals. This Material Safety Data Sheet (MSDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. Flinn Scientific Inc. assumes no legal responsibility for use or reliance upon this data.

# FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

# Improve Student Lab Results--Use Flinn Chemicals

flinn@flinnsci.com www.flinnsci.com P.O. Box 219 Batavia IL 60510 (800) 452-1261 Fax (866) 452-1436