

SAFETY DATA SHEET

1. Identification

Product identifier	Shakedown	
Other means of identification		
Product code	K6004	
Recommended use	Odor Eliminator	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	Distributor information	
Manufacturer		
Company name	Franklin Cleaning Technology	
Address	One Fuller Way	
	Great Bend, KS 67530 United States	
Telephone	Customer Service	(800) 810-4829
E-mail	Not available.	
Emergency phone number	CHEMTREC	(800) 424-9300
	Emergency	(620) 792-1711
	24 hour Emergency	(800) 424-9300
2. Hazard(s) identification		
Physical hazards	Not classified.	
Health hazards	Not classified.	
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Hazard symbol	None.	
Signal word	None.	
Hazard statement	The mixture does not meet the criteria for classification.	
Precautionary statement		
Prevention	Observe good industrial hygiene practices.	
Response	Wash hands after handling.	
Storage	Store away from incompatible materials.	
Disposal	Dispose of waste and residues in accordance with local authority requirements.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SODIUM BICARBONATE		144-55-8	20 - < 30
White Mineral Oil		8042-47-5	1 - < 3
Other components below reportable levels			70 - < 80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symptoms occur.	
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.	
Indication of immediate medical attention and special treatment needed	Treat symptomatically.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	

media	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Collect dust using a vacuum cleaner equipped with HEPA filter. Minimize dust generation and accumulation. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Avoid breathing dust. Avoid contact with eyes. Avoid prolonged exposure. Practice good housekeeping.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
White Mineral Oil (CAS 8042-47-5)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limit Va Components	alues Type	Value	Form
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to C	hemical Hazards		
Components	Туре	Value	Form
White Mineral Oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
·	TWA	5 mg/m3	Mist.
logical limit values	No biological exposure limits noted for the in	gredient(s).	

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Use tight fitting goggles if dust is generated.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

er i figerear ana eriennear p		
Appearance	Powder.	
Physical state	Solid.	
Form	Powder. Granular.	
Color	White	
Odor	Sea breeze	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not available.	
Flash point	Not available.	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	0.00001 hPa estimated	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Density	20.89 lbs/gal estimated	
Specific gravity	2.5 estimated	

Material name: Shakedown

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful. Inhalation of dusts may cause respiratory irritation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Dust in the eyes will cause irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
Information on toxicological eff	fects

Acute toxicity	Not available.	
Product	Species	Test Results
Shakedown (CAS Mixture)		
Acute		
Oral		
LD50	Rat	16230.7695 mg/kg estimated
* Estimates for product may b	e based on additional component data not shown.	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Dust in the eyes will cause irritation.	
Respiratory or skin sensitization	n	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. IARC Monographs. Overall Evaluation of Carcinogenicity White Mineral Oil (CAS 8042-47-5) 3 Not classifiable as to carcinogenicity to humans. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. This product is not expected to cause reproductive or developmental effects. **Reproductive toxicity** Not classified. Specific target organ toxicity single exposure Specific target organ toxicity -Not classified. repeated exposure Not available. Aspiration hazard **Chronic effects** Prolonged inhalation may be harmful. **Further information** This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results	
Shakedown (CAS Mixture)				
Aquatic				
Crustacea	EC50	Daphnia	4313.4844 mg/l, 48 hours estimated	
Fish	LC50	Fish	8051.6143 mg/l, 96 hours estimated	
* Estimates for product may be based on additional component data not shown.				
Persistence and degradability	No data is av	No data is available on the degradability of this product.		
Bioaccumulative potential	No data avail	No data available.		
Mobility in soil	No data avail	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.		

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are listed or exempted from listing on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - No

Immediate Hazard - No		
Delayed Hazard - No		
Fire Hazard - No		
Pressure Hazard - No		
Reactivity Hazard - No		

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

Material name: Shakedown

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. Massachusetts RTK - Substance List

White Mineral Oil (CAS 8042-47-5)

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

- US. Pennsylvania Worker and Community Right-to-Know Law White Mineral Oil (CAS 8042-47-5)
- US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

16. Other information, including date of preparation or last revision

Issue date	08-20-2014
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.